

17.02.2023

Consumer Information for primer caps

1. Use

1.1 Intended use:

Ignition devices.

1.2 Period of use:

The warranty period for primer caps is 2 years after production.

Use within 10 years after production under the exclusion of warranty.

1.3 Advices on safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Handle with care - avoid bumps, friction and impact.

Keep locked up and out of reach of children.

Wear eye glasses with side protection and ear protection.

The dismantling of the article is prohibited.

Thorough skin-cleansing after handling the product.

2. Storage:

Keep/Store only in original container.

Storage class: 1.4, Compatibility group: S.

Store cool and dry (Recommended storage temperature: 20°C (68 °F)).

Store in a place accessible by authorized persons only.

Do not store together with inflammable or other substances that mean an increase of risk.

3. Disposal:

Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with AVV:

Waste codes product: 16 04 03*

Waste name: Other waste explosives

Remark: Hazardous waste

Completely ignited articles may be recycled.

4. Legal information:
National regulations Germany:
Observe any national regulations, in particular:
- Explosives Act (SprengG)
- Weapons Act (WaffG)

International regulations:
Observe in addition any national regulations.

5. Declaration of conformity:
The following EC-Type Examination Certificates of the Federal Institute for Materials Research and Testing (BAM) are available:

Anvil primer cap	4,45 mm SINOXID:	0589.EXP.0678/06
Anvil primer cap	5,33 mm SINOXID:	0589.EXP.0679/06
Anvil primer cap	4,45 mm SINTOX:	0589.EXP.0681/06
Berdan primer cap	4,5 mm SINOXID:	0589.EXP.0683/06
Berdan primer cap	5 mm SINOXID:	0589.EXP.0864/06
Berdan primer cap	5,5 mm SINOXID:	0589.EXP.0685/06
Muzzle loader primer cap	3,95 mm SINOXID:	0589.EXP.4273/06
Muzzle loader primer cap	5,75 mm SINOXID:	0589.EXP.4274/06
Muzzle loader primer cap	6 mm SINOXID:	0589.EXP.3713/06
Medium	6,17 mm SINOXID:	0589.EXP.4272/06
Ignition VI	5,68 mm SINOXID:	0589.EXP.4267/06

Corresponding declarations of conformity you will find here:

<https://rws-ammunition.com/de/service/downloads>

Should you need any further information, please do not hesitate to contact us at:

info.ammotec@rws-tech.com